

**INTERNATIONAL ORGANISATION FOR STANDARDISATION
ORGANISATION INTERNATIONALE DE NORMALISATION
ISO/IEC JTC 1/SC 29/WG 2
MPEG TECHNICAL REQUIREMENTS**

ISO/IEC JTC 1/SC 29/WG 4 m71404

January 2025 – Geneva

Title: [VCM][CE0] Results of CE0.1

Source: Poznan University of Technology

Authors: Sławomir Rózek, Olgierd Stankiewicz, Sławomir Maćkowiak,
Tomasz Grajek, Maciej Wawrzyniak, Jakub Stankowski, Mateusz
Lorkiewicz, Marek Domański,

Abstract

This document contains the results of CE0 test 1 (CE0.1) - RoI-based coding tool turned off, performed between 148th and 149th MPEG meetings.

1. Procedure description

The purpose of CE0.1 test was to estimate the coding gain that comes from the RoI based coding tool of the VCM codec. This test can be done by coding and evaluation test datasets using VCM codec (VCMRS v0.11.1) with RoI module bypassed and comparison the results with the current anchor.

The test was performed following the CE0 description [1]. The coding scripts have been modified and committed to the dedicated branch for CE0 on Gitlab. During this test, there were no need to change any descriptors of any other tools.

We have done the encoding and evaluation using the machines with the following specification:

- Processor: Intel Core i7-12700K
- RAM: 32 GB
- GPU: nVidia RTX 4090.
- Operating System: Ubuntu 22.04 (updated)

2. Results

The detailed results can be found in the attached excel file. The summary is presented in the tables below.

Table 1. Results for the object detection task

Object Detection		End-to-End BD-Rate [%]					
		Inner			E2E		
		RA	LD	AI	RA	LD	AI
SFU-HW	Class A	13.25%	67.49%	9.60%	25.83%	35.53%	20.55%
	Class B	229.51%	130.85%	#####	157.69%	15.55%	95.65%
	Class C	-5.50%	-2.72%	30.09%	-11.49%	-15.52%	38.24%
	Class D	-3.54%	0.48%	9.94%	-5.26%	-29.02%	18.76%
	Average	55.47%	37.59%	#####	35.99%	-8.00%	44.63%
	Class O	435.92%	194.19%	#####	#####	112.04%	#####

Table 2. Results for the object tracking task

Object Tracking		End-to-End BD-Rate [%]					
		Inner			E2E		
		RA	LD	AI	RA	LD	AI
TVD	TVD-01-1	615.13%	238.44%	2787.97%	459.05%	171.82%	1410.38%
	TVD-01-2	475.70%	285.18%	2031.91%	514.05%	118.22%	1013.98%
	TVD-01-3	369.28%	141.37%	1948.66%	354.07%	7.97%	865.94%
	TVD-02-1	38.83%	23.90%	137.40%	38.43%	-13.00%	105.86%
	TVD-03-1	218.67%	33.71%	346.26%	186.25%	15.26%	839.22%
	TVD-03-2	248.33%	73.89%	359.90%	193.91%	28.77%	770.68%
	TVD-03-3	505.81%	234.98%	1514.33%	442.04%	147.36%	#####
	Average	353.11%	147.35%	1303.78%	312.55%	68.06%	#####

3. Acknowledgements

Thanks to China Telecom for crosschecking the experiment.

4. References

[1] ISO/IEC JTC 1/SC 29/WG 4, “VCM-CE 0: Tool experiments”, doc. N0594, November 2024, Kemer.